



COMPONENTS

QTY	ITEM
1	MAIN POST 3.288 M LONG
1	NR76 NETBALL RING WITH NET AND CORD
2	M8 X 30 MM S/S SOCKET HEAD COUNTERSUNK CAP SCREWS
SLEEVE OPTIONS	
1	ES76 - SLEEVE & EL76 - CAP
1	EHC76 - STEEL SLEEVE WITH HINGED LID

INSTALLATION INSTRUCTIONS:

- PLEASE REFER TO FOOTING DRAWINGS FOR DETAILS OF THE FOOTING.
CONCRETE SHOULD BE AS SPECIFIED AND FOOTING IS SUITABLE FOR CLASS 'S' & 'M' SITES ONLY. MUST BE RE-ENGINEERED FOR DIFFERENT SOIL TYPES.
- WHILE INSTALLING THE FOOTINGS ON THE GROUND, ENSURE THAT THE BOLT ON THE SLEEVE IS IN CORRECT POSITION AS SHOWN.
- THE POSITION OF THE GROUND SLEEVE SHOULD BE IN REFERENCE TO THE COURT LINE MARKINGS. ALIGN THE INSIDE OF THE SLEEVE WITH THE COURT BASE LINE.
 LET THE CONCRETE SET AND CURE FOR FEW DAYS BEFORE INSTALLING THE NETBALL POST.
- ATTACH THE SUPPLIED SUPPLIED NETBALL RING TO THE POST USING M8 X 30 MM S/S SOCKET HEAD COUNTERSUNK SCREWS. THE RING SHOULD BE IN THE ORIENTATION AS SHOWN IN THE DIAGRAM ONLY.
- THEN INSERT THE POST INTO THE GROUND SLEEVE WITH RING FACING THE PLAYING FIELD.

TITLE: NS76c NETBALL POLE	
DRAWING NUMBER: NS76c ASSEMBLY	
WEIGHT: -	CUBIC MEASURE -



Oz Ring Pty Ltd
 Trading as:
Play Hard Sports Equipment
 ABN 79 066 094 559
 24 Ern Harley Drive
 Burleigh Heads Qld 4220
 Phone: (07) 5593 4494
 Fax: (07) 5593 4338
 Website: www.playhardsports.com.au
 Email: email@playhardsports.com.au