



**INSTALLATION INSTRUCTIONS:**

- PLEASE REFER TO FOOTING DRAWINGS FOR DETAILS OF THE FOOTING. **CONCRETE SHOULD BE AS SPECIFIED AND FOOTING IS SUITABLE FOR CLASS 'S' & 'M' SITES ONLY. MUST BE RE-ENGINEERED FOR DIFFERENT SOIL TYPES.**
- WHILE INSTALLING THE FOOTINGS ON THE GROUND, ENSURE THAT THE BOLT ON THE SLEEVE IS IN CORRECT POSITION AS SHOWN.
- THE POSITION OF THE GROUND SLEEVE SHOULD BE IN REFERENCE TO THE COURT LINE MARKINGS. ALIGN THE INSIDE OF THE SLEEVE WITH THE COURT BASE LINE.  
LET THE CONCRETE SET AND CURE FOR FEW DAYS BEFORE INSTALLING THE NETBALL POST.

**FOR NETBALL POST**

- SLIDE THE COLLAR OVER THE TELESCOPIC POLE.
- ATTACH THE NR60 RING TO THE TELESCOPIC POLE USING M8 X 30 MM S/S SOCKET HEADED COUNTERSUNK CAP SCREWS IN SUCH A WAY THAT THE LOCATING HOLE AND THE RING AND FACING IN OPPOSITE DIRECTION.
- INSERT THE NETBALL POST ASSEMBLY INTO THE GROUND SLEEVE WITH THE RING FACING TOWARDS THE PLAYING FIELD.

**OPERATION:**

- ADJUST THE HEIGHT FOR JUNIOR OR SENIOR SETUP USING THE KNOB ON TOP OF BASE POLE.
- WHILE SETTING SENIOR HEIGHT, DO NOT EXTEND PAST THE PAINTED LINE.
- WHEN NOT IN USE COVER THE SLEEVE WITH THE SLEEVE CAP SUPPLIED.

QTY	ITEM DESCRIPTION
1	BASE POLE (1.77M LONG)
1	TELESCOPIC POLE (1.837M LONG)
1	NR60 NETBALL RING
1	NETBALL NET, CORD & INSTRUCTIONS
1	M12 X 20 MM LOBE KNOB
1	NS76T COLLAR
2	M8 X 30 MM S/S SOCKET HEADED COUNTERSUNK CAP SCREWS
<b>OPTIONS FOR SLEEVES</b>	
1	ES76 SLEEVE AND EL76 CAP
1	EHC76 STEEL SLEEVE WITH HINGED CAP

TITLE: NS76Tc  
NETBALL POST

DRAWING NUMBER: ASSEMBLY

WEIGHT: - CUBIC MEASURE: -

Oz Ring Pty Ltd  
Trading as:  
Play Hard Sports Equipment  
ABN 79 066 094 559  
24 Ern Harley Drive  
Burleigh Heads Qld 4220  
Phone: (07) 5593 4494  
Fax: (07) 5593 4338  
Website: [www.playhardsports.com.au](http://www.playhardsports.com.au)  
Email: [email@playhardsports.com.au](mailto:email@playhardsports.com.au)